

CNG Nozzles



NGV1 compatible, 3600 psi (248.2 bar) compressed natural gas dispensing nozzle for quick-fill applications.

- Ergonomic, single-hand design for easy connecting and disconnecting.
- Swivels at inlet fitting.
- Comes standard with yellow scuff guard.
- JawLoc design prevents receptacle wear.
- PressureLoc sleeve prevents disconnection at high pressures.
- Outer sleeve anodized to prevent corrosion.
- Tamper-proof design prevents unauthorized disassembly.
- Light-weight construction compared to similar nozzles.
- Designed for use with shorter pipe nipple / dispensing hose which allows easier access to the fuel pocket and clearance of the 3-way ball valve.
- Easy grip sleeve for better access to fuel pocket.
- Nozzle covered by a one (1) year warranty.

New Nozzles

| MODEL NO. | DESCRIPTION | SHIPPING WEIGHT LBS (KG) |
|-----------|--|--------------------------|
| 8695 | Type 2A Compressed Natural Gas Dispensing Nozzle | 2 (0.9) |

Construction

| | |
|-------|--|
| Body | Aircraft-grade aluminum body with stainless steel locking jaws Chromate conversion coating (Alodine) internal parts |
| Seals | Fluorocarbon with PTFE backup rings |
| Inlet | 1/16-18 UNF, SAE J1926-1 O-ring port |



**Husky**

GENERAL FUELING PRODUCTS

CNG Nozzles

NGV1 compatible, 3600 psi (248.2 bar) compressed natural gas dispensing nozzle for quick-fill applications.

Dimensions



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

