XS® MFM Nozzles



Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- A reinforced stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.

- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.

New Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159562	with Three Notch Hold Open Clip Splash Guard	and Waffle 3.3 (1.4)
159568	without Hold Open Clip, with Red Lenticular Lens	d VSG, Sightglass and 3.0 (1.3)
E159560	with Three Notch Hold Open Clip Waffle Splash Guard	, Mate Guard and 3.3 (1.4)


New Light Duty Diesel Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
159560	with Three Notch Hold Open Clip Splash Guard	and Waffle 3.3 (1.4)
539660	with Three Notch Hold Open Clip and Waffle Splash Guard	, Double Poppet 3.3 (1.4)
1595267	with Three Notch Hold Open Clip Less Spout	, and Drip 3.3 (1.4)

CONSTRUCTION

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPT











WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
002276	1" F x 1" F NPT Reconnectable Safe-T-Break®
005812	1" F x 1" F NPT Non-Reconnectable Safe-T-Break®
006301	1" F x 1" F NPT Non-Reconnectable PCC Safe-T-Break®
005231	1" F x 1" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000087	1" M x 1" F NPT Multi-Plane Swivel
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel
000095	1" M x 1" F NPT 70° Pump Swivel
003395	1" M x 1" F NPT Multi-Plane Restricted Swivel
000352	1" M x ¾" F NPT Multi-Plane Swivel
000356	1" M x ¾" F NPT Multi-Plane Swivel Anodized Black

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
005969	1" M NPT Multi-Plane Swivel connected to 1" F NPT Reconnectable Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop® with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
007089	Nozzle Service Kit
003593	Hold Open Clip Kit
000397	Unleaded Spout Gauge
000385	1" M x ¾" F Reducer Bushing



Guards

MODEL NO.	DESCRIPTION
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069 (800) 325-3558 • Fax (636) 825-7300 www.husky.com • sales@husky.com

