# EagleFlex® Farm Tank



#### **Gasoline Hose Assemblies with Static Wire.**

- Designed for durability and flexibility.
- · Oil and abrasion resistant.
- · Supplied with static wire.
- Recommended for use with electric pumps.
- Static wire hose always recommended with electric motors.
- Designed for use in agricultural, industrial and construction maintenance applications.
- Engineered for dispensing gasoline, diesel, kerosene and oil from farm and barrel-type pumps where UL approval is not required.

- Curb pump hose recommended for:
  - UL Listed hose material requirements.
  - For high aromatics or severe applications.
- All Farm Tank hose assemblies are 100% inspected for electrical continuity.
- Do not use these hoses at a service station or to refuel aircraft.

# **Farm Fueling Hoses**

MODEL NO.	DESCRIPTION	SHIPPING WEIGH	IT LBS (KG)
3/4" HOSES			
FT012S10	3/4" x 10' Far	m Tank Assembly Hose Bulk	2.9 (1.3)
FT012S12	3/4" x 12' Far	m Tank Assembly Hose Bulk	3.5 (1.6)
FT012S12B	3/4" x 12' Far	m Tank Assembly Hose Boxed	3.5 (1.6)
FT012S14	3/4" x 14' Far	m Tank Assembly Hose Bulk	4.1 (1.9)
FT012S14B	3/4"x 14' Farn	n Tank Assembly Hose Boxed	4.1 (1.9)
FT012S15	3/4" x 15' Far	m Tank Assembly Hose Bulk	4.4 (2.0)
FT012S15B	3/4" x 15' Far	m Tank Assembly Hose Boxed	4.4 (2.0)
FT012S17	3/4" x 17' Far	m Tank Assembly Hose Bulk	4.9 (2.2)
FT012S20	3/4" x 20' Far	m Tank Assembly Hose Bulk	5.8 (2.6)
FT012S20B	3/4" x 20' Far	m Tank Assembly Hose Boxed	5.8 (2.6)
1" HOSES			
FT016S10	1" x 10' Farm	Tank Assembly Hose Bulk	4.5 (2.0)
FT016S12	1" x 12' Farm	Tank Assembly Hose Bulk	5.4 (2.4)
FT016S12B	1" x 12' Farm	Tank Assembly Hose Boxed	5.4 (2.4)
FT016S14	1" x 14' Farm	Tank Assembly Hose Bulk	6.3 (2.9)
FT016S15	1" x 15' Farm	Tank Assembly Hose Bulk	6.8 (3.1)
FT016S15B	1" x 15' Farm	Tank Assembly Hose Boxed	6.8 (3.1)
FT016S17	1" x 17' Farm	Tank Assembly Hose Bulk	7.7 (3.5)
FT016S20	1" x 20' Farm	Tank Assembly Hose Bulk	9.0 (4.1)
FT016S20B	1" x 20' Farm	Tank Assembly Hose Boxed	9.0 (4.1)
FT016S25	1" x 25' Farm	Tank Assembly Hose Bulk	11.3 (5.1)

## Construction

Tube	NBR, RMA Class A
Cover	NBR/PVC RMA Class A
Reinforcement	Spiral high tensile strength polyester cord
Temperature Range	-20°F to +160°F (-29°C to +71°C)







Gasoline Hose Assemblies with Static Wire.

# **System Options**

#### **Available in these Sizes**

ID		NOM OD		WEIGHT	
Size	MM	IN	MM	LB/FT	KG/M
3/4"	19	1.13	29	0.29	0.43
1"	25	1.38	35	0.45	0.67

### Couplings

Permanent externally crimped 3/4" and 1" NPT.



