



TECHNICAL BULLETIN

Thread sealant now offered with Husky conventional hanging hardware



Conventional hanging hardware connections are designed with National Pipe Thread (NPT) connections. NPT thread connections require the application of thread sealants to ensure a leak free connection while in service. Husky Corporation now offers the option of convenient 1/8 ounce tubes of Gasoila® brand thread sealant with selected conventional nozzles, swivels, and safe-t-breaks.

Application is simple- Thoroughly mix Gasoila® sealant by moving sealant back and forth in tube with fingers. Tear open end of tube and apply sealant liberally to the male threads prior to assembling connection. Tighten the connection securely and inspect for leaks prior to putting fueling point into service. Discard tube and installation is finished. An MSDS sheet for Gasoila® sealant is available via the Husky website.

Below are current products available with the Gasoila® thread sealant option.

April 2008

**1+XS AUTOMATIC PRESSURE ACTIVATED NOZZLES W/ WAFFLE
SPLASH GUARD W/ GASOILA***

159559G UNLEADED W/ HOLD OPEN CLIP

159561G LEADED W/ HOLD OPEN CLIP

**1+XS MFM AUTOMATIC PRESSURE ACTIVATED NOZZLE W/ WAFFLE
SPLASH GUARD W/ GASOILA - 1" INLET**

159562G UNLEADED W/ HOLD OPEN CLIP

159560G LEADED W/ HOLD OPEN CLIP

1A AUTOMATIC NOZZLES W/ GASOILA

209803G LEADED W/ HOLD OPEN CLIP

CONVENTIONAL / HIGH FLOW / FARM SWIVELS W/ GASOILA

0350G 1+VI MULTI-PLANE 3/4" M X 3/4" F W/ GASOILA

4860G HEAVY DUTY HIGH FLOW 1" M X 1" F W/ GASOILA

0087G VI-T MULTI-PLANE HI-FLOW 1" M X 1" F W/ GASOILA

SAFE-T-BREAKS® W/ GASOILA

3360G RECONNECTABLE SAFE-T-BREAK® W/ GUARD 3/4"F X 3/4"F W/ GASOILA

2276G RECONNECTABLE SAFE-T-BREAK® W/ GUARD 1"F X 1"F W/ GASOILA

For further information or questions about this product option please contact Joe Laschke
Husky Technical Service Representative at jaschke@husky.com or our customer service
department at 800-325-3558