## **EagleFlex**®



### **E0-E85 Curb Pump Hose.**

- Recommended for use with Ethanol blends from E0 to E85.
- · Resistant to crushing and stands up to run-over.
- · Highly resistant to cuts, abrasions, sun and weather.
- · Flexibility of a softwall, durability of a hardwall.
- · Assures accurate readings at the pump.
- · Will not mark or scratch vehicle finishes.

- · Hose material is private branded and UL Listed to UL 330A and CAN/ ULC-S612-99.
- · All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.

### **E0-E85 Wirebraid Hoses**

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG
3/4" HOSES		
CP12ET04	3/4" E0-E85 4' A	ssembly Hose 1.7 (0.8
CP12ET05	3/4" E0-E85 5' A	ssembly Hose 2.1 (1.0
CP12ET06	3/4" E0-E85 6' A	ssembly Hose 2.5 (1.1
CP12ET09	3/4" E0-E85 9' A	ssembly Hose 3.8 (1.7
CP12ET10	3/4" E0-E85 10'	Assembly Hose 4.2 (1.9
CP12ET10X	3/4" E0-E85 10'	Assembly Hose Bulk 4.2 (1.9
CP12ET12	3/4" E0-E85 12'	Assembly Hose 5.0 (2.3
CP12ET12X	3/4" E0-E85 12'	Assembly Hose Bulk 5.0 (2.3
CP12ET14	3/4" E0-E85 14'	Assembly Hose 5.9 (2.7
CP12ET16	3/4" E0-E85 16'	Assembly Hose 6.7 (3.0
CP12ET20	3/4" E0-E85 20' A	Assembly Hose 8.4 (3.8
CP12ET50X	3/4" E0-E85 50' A	Assembly Hose Bulk 21.0 (9.5

#### Construction

Tube	Black Nitrile
Cover	Black CPE (cholrinated polyethylene), wrap impression
Reinforcement	One wirebraid with full diameter grounding sheath
Temperature Range	-40°F to +180°F (-40°C to +82°C)

GEFICK® ET 3/4 EO-E85 HOSE PU MH20477 Ma







WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



# EagleFlex® E0-E85

E0-E85 Curb Pump Hose.

### **System Options**

#### **Available in these Sizes**

ID		NOM OD		MAX WP		WEIGHT	
Size	мм	IN	мм	PSI	MPA	LB/FT	KG/M
3/4"	19	1.10	28	150	1.03	0.42	0.63

### **Couplings**

Permanent externally crimped nickel-plated stems, zinc ferrules.





