

# 4113 Reuseable



**4113 with Reusable couplings aviation fueling hose recommended for all types of riser deck, reel, and hydrant hose applications.**

- Used for commercial and private aircraft
- Resistant to jet fuel and higher aromatic aviation gasolines
- Compatible with use on hydrant service
- Meets EI 1529, 7th Edition, 2014 and European Standard EN ISO 1825 (2011), Type C, Grade 2, NFPA 407
- Recommended for all types of riser deck, reel, and hydrant hose applications
- All aviation hose assemblies are 100% hydrostatic tested to 600 PSI and inspected for electrical continuity
- Every hose receives a unique serial number and test certificate
- Standard hose assemblies are supplied with Roman Seliger brand 4-bolt aluminum clamp reusable couplings. Elaflex Spannloc are available on request.
- All 4" ID hoses utilize Roman Seliger 4-bolt aluminum clamped reusable fittings.

## Specifying Information

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
<b>1 1/2" HOSES</b>		
CP240720HKGB	1 1/2" X 60' 4113 MXF BSP SS RU	51.6 (23.5)
CP240792HEGA	1 1/2" X 66' 4113 MXF NPT BR RU	56.8 (25.8)
<b>2" HOSES</b>		
CP320720HKGB	2" x 60' 4113 MXF BSP SS RU	72.0 (32.7)
CP320720HKGA	2" x 60' 4113 MXF BSP BR RU	72.0 (32.7)
CP320792HEGA	2" x 66' 4113 MXF NPT BR RU	79.2 (36.0)
<b>2 1/2" HOSES</b>		
CP400120HEGD	2 1/2" x 10' 4113 MXF BSP TP RU	16.9 (7.7)
CP400144HEGD	2 1/2" x 12' 4113 MXF BSP TP RU	20.3 (9.2)
CP400156HDGB	2 1/2" x 13' 4113 MXM NPT SS RU	22.0 (10.0)
<b>3" HOSES</b>		
CP480144HEGD	3" x 12' 4113 MXF BSP TP RU	28.0 (12.7)
CP480168HABA	3" x 14' 4113 MXM NPT BR RU	32.6 (14.8)
CP480240HEGD	3" x 20' 4113 MXF BSP TP RU	46.6 (21.2)
CP480300HEGD	3" x 25' 4113 MXF BSP TP RU	58.3 (26.5)
CP480396HDGB	3" x 33' 4113 MXM NPT SS RU	76.9 (36.3)
CP480480HEGD	3" x 40' 4113 MXF BSP TP RU	93.2 (42.4)
<b>4" HOSES</b>		
CP640144HEGD	4" x 12' 4113 MXF BSP TP RU	39.6 (18.0)
CP640394HEGD	4" x 32.8' 4113 MXF BSP TP RU	108.2 (49.2)
CP640432HKGD	4" x 46' 4113 MXF BSP TP RU	151.8 (69.0)

## Construction

Tube	Black nitrile synthetic rubber
Cover	Black neoprene static dissipating/static conductive synthetic rubber (wrapped finish)
Reinforcement	Spiral-plyed (4) synthetic fabric and one nylon breaker



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



# 4113 Reusable

**4113 with Reusable couplings aviation fueling hose recommended for all types of riser deck, reel, and hydrant hose applications.**

## Available in these Sizes

ID	NOM OD		MAX WP		WEIGHT		
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
3/4"	19	1.25	31.8	300	2.07	0.50	0.75
1"	25	1.50	38.0	300	2.07	0.62	0.93
1 1/4"	32	1.78	45.2	300	2.07	0.79	1.18
1 1/2"	38	2.06	52.3	300	2.07	0.86	1.28
2"	50	2.57	65.3	300	2.07	1.20	1.79
2 1/2"	63	3.20	81.2	300	2.07	1.69	2.52
3"	75	3.70	94.0	300	2.07	2.33	3.47
4"	102	4.94	125.0	300	2.07	3.30	4.92

## Couplings

Permanent	Brass male and female NPT (swivel nut)
Reusable 4-bolt	Aluminum clamp fittings - male and female, NPT and BSP threads - all females have swivel nuts - available with brass, tin plated brass, and stainless inserts Aluminum male available for 2, 2 1/2 and 3-inch ID

## Protective Coils

9746	2" Banding Coil, White
9744	3" Banding Coil, White
9774	4" Banding Coil, White
9793	3" Banding Coil, Orange

## Order Guide (Ex. CP320600HABA)

### AVIATION HOSE SIZE - CPSS

3/4" = CP12	2" = CP32
1" = CP16	2 1/2" = CP40
1 1/4" = CP20	3" = CP48
1 1/2" = CP24	4" = CP64

### HOSE LENGTH (IN INCHES) - LLLL

0600 = 50 feet 0 inches
0606 = 50 feet 6 inches

### AVIATION HOSE - H or J

H = 4113 Aviation Hose
J = 5500 JacRiser Hose

### NOTE:

If special, the next two digits will be used sequentially first using numbers (0-9) then using Alpha (A-Z). Special fittings or special materials will be described in the fab/shipping instructions section of the factory order. See separate assembly drawing for each special assembly number.

### FITTING STYLE - S

A = Male x Male NPT Not Reusable
B = Male x Female NPT not Reusable
C = Female x Female NPT Not Reusable
D = Male x Male NPT Reusable
E = Male x Female NPT Reusable
F = Female x Female NPT Reusable
J = Male x Male BSP Reusable
K = Male x Female BSP Reusable
L = Female x Female BSP Reusable
S = Special (See Note 1)

### FITTING BRAND - F

A = Internal Expansion Permanent (stainless steel only)
B = Dixon/UMI Internal Expansion (Permanent (Brass Insert))
D = Dixon Swaged
E = Dixon Reusable
F = Elaflex Resuable
G = Roman Seliger Reusable

### INSERT MATERIAL - M

A = Brass
B = Stainless Steel
D = Tin-Plated Brass
F = Carbon Steel

### OVERALL LENGTH - O

For all sizes except CP64, if "0" is present, LLLL = OAL
For CP64 only, if blank, LLLL = OAL
For CP64 only, if "C" present, LLLL = Cut Length



2325 Husky Way • Pacific, MO 63069  
(800) 325-3558 • Fax (636) 825-7300  
[www.husky.com](http://www.husky.com) • [sales@husky.com](mailto:sales@husky.com)

MADE IN THE U.S.A.