EagleFlex® E0-E25

Husky
GENERAL FUELING PRODUCTS

E0-E25 Curb Pump Hose.

- Recommended for use with Ethanol blends from E0 to E25.
- Resistant to crushing and stands up to run-over.
- Highly resistant to cuts, abrasions, sun and weather.
- Flexibility of a softwall, durability of a hardwall.
- Assures accurate readings at the pump.
- Will not mark or scratch vehicle finishes.
- Hose material is private branded and UL Listed to UL 330 and CAN/ULC-S612-99.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.

E0-E25 Wirebraid Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3/4" HOSES		
CP12EH06L	3/4" E0-E25 6' Assembly Hose	2.5 (1.1)
CP12EH08.5L	3/4" E0-E25 8.5' Assembly Hose	3.4 (1.5)

Construction

Tube	Black Nitrile
Cover	Black CPE (cholrinated polyethylene), wrap impression
Reinforcement	One wirebraid with full diameter grounding sheath
Temperature Range	-40°F to +180°F (-40°C to +82°C)



ISO 9001:2015 CERTIFIED COMPANY

c UL us

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EagleFlex® E0-E25

E0-E25 Curb Pump Hose.

System Options

Available in these Sizes

ID		NOM OD		MAX WP		WEIGHT	
Size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
3/4”	19	1.10	28	150	1.03	0.42	0.63

Couplings

Permanent externally crimped zinc stems, aluminum ferrules.



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.