

# TM3 Valve



**TM3 Air Shut-off Valve for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.**

- Fully pneumatic - no electronic parts.
- Avoid costly overflows or untimely inventory shortages.
- Ideal for tanks with baffles.
- Engineered for most single or double walled above ground storage tanks.
- Aluminum float is not affected by oils or most other chemicals.
- Shuts off air supply to pumps preventing tank overflows.
- Easy installation.
- Operating range 30-200 PSI.

### New Valves

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
007700	TM3 Pneumatic Shut Off Valve	4.7 (2.1)






TM3 Air Shut-off Valve for use with oil, waste oil, diesel fuel, antifreeze, water and other fluids with a high flash point.

## Dimensions and System Options

### Replacement Parts

MODEL NO.	DESCRIPTION
007553	TM3 Replacement Chain
011425	TM3 Replacement Float
007774	TM3 Weight



2325 Husky Way • Pacific, MO 63069  
(800) 325-3558 • Fax (636) 825-7300  
[www.husky.com](http://www.husky.com) • [sales@husky.com](mailto:sales@husky.com)

MADE IN THE U.S.A.