

V34 DP Nozzles



Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

- V34 nozzle shuts off when the gas tank is full.
- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- *Streamshaper*® reduces turbulence for straighter fuel flow and less splash back spillage.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Uses conventional spout with spout ring and soft vapor escape guard.
- Vapor assist achieved at the body end of the spout where a vapor ring catches emissions.
- Nozzle spout is covered by a one year warranty.



New Unleaded Nozzles



MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6252041	with Double Poppet and Two Notch Hold Open Clip	4.0 (1.8)
6252041A*	with Double Poppet and Two Notch Hold Open Clip - Atex	4.0 (1.8)
6252931A*	with High Flow Double Poppet and Two Notch Hold Open Clip - Atex	4.0 (1.8)

Rebuilt Unleaded Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
6254041	with Three Notch Hold Open Clip	3.7 (1.6)
6254241	with Three Notch Hold Open Clip and Sightglass	3.7 (1.6)
6254081	without Hold Open Clip	3.7 (1.6)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Fiber reinforced Teflon®
Lever	One piece contoured steel with hard plastic cover
Inlet	M34 x 1.5



California Environmental Protection Agency

AIR RESOURCES BOARD



II 1 G
EN13012
Type 1



P-TÜ7-8113626964



V34 DP Nozzles

Pressure activated, automatic shut-off vacuum assist nozzle for full-service, self-service and unattended stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
004034	Reconnectable Safe-T-Break®
006210	Non-Reconnectable Safe-T-Break®
010513	Non-Reconnectable Safe-T-Break® - Shearpin

Swivels

MODEL NO.	DESCRIPTION
004605	Inverted Vapor Assist Swivel
004605A	Inverted Vapor Assist Swivel - Atex

Spouts


MODEL NO.	DESCRIPTION
006291	Complete Spout Assembly Kit - Unleaded
006391	Unleaded Spout

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004360	Air/Liquid Spout Adaptor
003593	Hold Open Clip Kit
007089	Nozzle Service Kit
005233	O-ring Kit
005260	Tool for dry Air/Liquid Test
000397	Unlead Spout Gauge
005837	Vapor Assist Flo-Equalizer®
004000	Vapor Splash Guard (VSG) with Clamp
004039	VSG Clamp
006497	VSG Clamp Tool



Guards

MODEL NO.	DESCRIPTION
006951	Full Grip Guard
004231	Full Grip Reguard
005494	Lever Guard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
007220	POPD® S Full Grip Reguard



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.